

Taper Roller Bearings

Thrust
Inch Series



Dimensions				Load Rating		Bearing
mm				kN		
d	D	B	r	Dynamic (C)	Static (C ₀)	
76.200	161.925	33.338				T 311
111.760	223.520	55.880	3.3	91.2	87.9	T 441
127.000	266.700	58.738	4.8	86.7	83.6	T 511
128.588	266.700	58.738	4.8	100.0	107.0	T 511 A
127.000	250.825	55.562	4.8	122.0	121.0	T 520
152.400	317.500	69.850	4.8	141.0	148.0	T 611
165.100	311.150	88.900	6.4	185.0	199.0	T 651
168.275	304.800	69.850	6.4	193.0	212.0	T 661
174.625	358.775	82.550	6.4	224.0	246.0	T 691
177.800	368.300	82.550	8.0	294.0	336.0	T 711
203.200	419.100	92.075	8.0	380.0	440.0	T 811
228.600	431.800	88.773	9.7	457.0	1124.1	T 9020
228.600	482.600	104.775	11.2	391.0	462.0	T 911
234.950	482.600	104.775	11.2	391.0	462.0	T 911 A
234.950	546.100	127.000	16.0	455.0	546.0	T 921
190.500	368.300	92.250	8.7	429.0	517.0	T 9727
206.375	419.100	120.650	11.4	591.0	744.0	T 9848
241.300	496.300	127.000	16.0	475.0	599.0	T 9936
260.000	360.000	92.000	1.0	650.0	841.0	350981 C [*]
273.050	552.450	132.715	6.4	4372.0	20777.0	N 3243 A
350.000	490.000	130.000	1.1	990.0	4650.0	351100 C ¹